AD-A046 676 NAVY UNDERWATER SOUND LAB NEW LONDON CONN F/G 17/1
CALCULATED AZIMUTHAL DIRECTIVITY PATTERNS FOR SEVERAL FREQUENCI--ETC(U)
AUG 61 G T ADKINS

UNCLASSIFIED USL-TM-932-178-61 NL

| OF |
ADA
046676



END
DATE
FILMED
12-77
DDC

MOST Project

Copy 2 of 28 Copies

USL Problem
No. 1-651-00-00

U. S. Navy Underwater Sound Laboratory
Fort Trumbull, New London, Connecticut

THIS COPY FOR BuShips 689C

CALCULATED AZIMUTHAL DIRECTIVITY PATTERNS FOR SEVERAL FREQUENCIES USED IN SCANNING SONARS.

by

George T. Adkins

USL Technical Memorandum No. 932-178-61

3 Aug[redacted]1961

22p.

DDC
RECEIVED
NOV 21 1977
A

AD A046676

COPY AVAILABLE TO DDC DOES NOT PERMIT FULLY LEGIBLE PRODUCTION

INTRODUCTION

This memorandum presents calculated directivity patterns, for several frequencies, for scanning sonars that have 48 stave transducers and use 12 or 16 staves for forming the acoustic beams. Constant time delay type beam forming networks were assumed in the computations for one set of patterns, constant phase shift type beam forming networks for the other. The shading used in the 16 stave calculations includes a cosine squared function and the shading derived from a typical single stave beam pattern; the shading for the 12 stave calculations is based on only single stave shading.

The computations assumed that transducer staves were spaced a half wave length ~~(λ/2)~~ apart (for 5 Kc.). The basic computations were made by the Theory and Analysis Branch of the Laboratory.

DISCUSSION

Figures (1) through (5) present the calculated beam patterns for the different frequencies for the 16 stave receiving beam and a constant time delay beam forming network. Noted on these figures are the first and second minor lobes, and their level relative to that of the major beam. Also noted on each figure, are the beam widths at the 3 db and 6 db down points. Figures (1) through (5) show that up to 20% increases in frequency have little effect on the acoustic beam.

Figures (6) through (9) present the calculated beam patterns for the different frequencies for a 16 stave receiving beam and a constant phase shift type beam forming network.

Figures (10) through (14) presents the calculated beam patterns for the different frequencies for the unshaded 12 stave beams and a constant time delay beam forming network. The beam patterns themselves are acceptable; however, it should be noted that the first minor lobes are down only 14 db as compared to about 20 db for 16 stave receiving beams.

DISTRIBUTION STATEMENT A
Approved for public release;
Distribution Unlimited

AD No. 932-178-61
DDC FILE COPY

254 200 Encl 1 to USL ltr ser 932-180

Figures (19) and (20) present the relative on-axis response in db versus frequency for the 16 and 12 stave patterns and for constant phase shift type and constant time delay type beam forming networks. For the 12 stave patterns with the constant phase shift type, the response drops off .7 of a db at 6.0 Kc, for the same condition, the 16 stave response drops off -1.5 db. No drop is experienced with the constant time delay system.

CONCLUSIONS

The constant phase shift beam forming arrangement appears to be limited as to how much the stave spacing can vary from $\lambda/2$ and still be satisfactory.

George T. Adkins per mf

GEORGE T. ADKINS
Electronic Technician

ACCESSION for
NTIS White Section
DDC Buff Section
UNANNOUNCED
JUSTIFICATION
BY
DISTRIBUTION/AVAILABILITY CODES
Dist. AVAIL. and/or SPECIAL
A 23 0.4



FIG 1

NO. 3124. POLAR CO-ORDINATE.
CODEX BOOK COMPANY, INC., NORWOOD, MASSACHUSETTS.
PRINTED IN U.S.A.



NO 3124 POLAR CO-ORDINATE

CODA BOOK COMPANY, INC. NORWOOD, MASS. (TUSCETTS)
PRINTED IN U.S.A.

USL Tech Memo No. 932-178-61 of 28 July 1961

FIG 2



USL Tech Memo No. 932-178-61 of 28 July 1961

FIG. 3

NO. 3124. POLAR CO-ORDINATE. COLLEK BOOK COMPANY, INC., NORWOOD, MASSACHUSETTS. PRINTED IN U.S.A.


8°
12°
20db DOWN
27db DOWN
RELATIVE RESPONSE VERSUS BEARING
FREQ 5.25 KC (±5%)
16 STAVES KA'S EQUAL
(Cos)² + Cos PATTERN. SHADING
CONSTANT TIME DELAY TYPE
BEAM FORMING NETWORK
SCALE = 10 db PER INCH
USL Tech Memo No. 932-178-61 of 28 July 1961
FIG 4



CODEX BOOK COMPANY, INC. NORWOOD, MASSACHUSETTS.
PRINTED IN U.S.A.
NO. 3124. POLAR CO-ORDINATE.



CODEX BOOK COMPANY, INC., NORWOOD, MASSACHUSETTS
PRINTED IN U.S.A.
NO. 3124. POLAR COORDINATE.

USL Tech Memo No. 932-178-61 of 28 July 1961

FIG 6


30° 330°
20° 340°
10° 350°
0
350° 10°
340° 20°
330° 30°
40° 320°
320° 40°
50° 310°
310° 50°
60° 300°
300° 60°
70° 290°
290° 70°
80° 280°
280° 80°
90° 270°
270° 90°
100° 260°
260° 100°
110° 250°
250° 110°
120° 240°
240° 120°
130° 230°
230° 130°
140° 220°
220° 140°
150° 210°
160° 200°
170° 190°
180°
190° 170°
200° 160°
210° 150°
8°
12°
RELATIVE RESPONSE VERSUS BEARING
FREQ 5.75 KC (11.5%)
(COS)² & COS PATTERN SHADING
16 STAVES KAS UNEQUAL
CONSTANT PHASE SHIFT TYPE
BEAM FORMING NETWORK
SCALE = 10 db PER INCH
USL Tech Memo No. 932-17B-61 of 28 July 1961
FIG 7
CODEX BOOK COMPANY, INC. NORWOOD, MASSACHUSETTS.
PRINTED IN U.S.A.
NO. 3124. POLAR CO-ORDINATE.



NO. 3124. POLAR CO-ORDINATE.

USL Tech Memo No. 932-178-61 of 28 July 1961

FIG. 8



CODEX BOOK COMPANY, INC., NORWOOD, MASSACHUSETTS.
PRINTED IN U.S.A.
NO. 3124. POLAR CO-ORDINATE.



USL Tech Memo No. 932-178-61 of 28 July 1961

FIG 10

CODEX BOOK COMPANY, INC. NORWOOD, MASSACHUSETTS
PRINTED IN U.S.A.
NO. 3124. POLAR CO-ORDINATE.



USL Tech Memo No. 932-178-61 of 28 July 1961

FIG 11



USL Tech Memo No. 932-178-61 of 28 July 1961

FIG. 12


9°
13°
13.5 db down
18.5 db down
RELATIVE RESPONSE VERSUS BEARING
FREQ 5.25 KC (+5%)
12 STAVES KA'S EQUAL
COSINE PATTERN SHADING
CONSTANT TIME DELAY TYPE
BEAM FORMING NETWORK
SCALE = 10 db PER INCH
USL Tech Memo No. 932-178-61 of 28 July 1961
FIG 13
CODEX BOOK COMPANY, INC. NORWOOD, MASSACHUSETTS. PRINTED IN U.S.A.
NO 3124. POLAR COORDINATE.


10°
15°
14db down
19db down
RELATIVE RESPONSE VERSUS BEARING
FREQ 5KC
12 STAVES KA'S EQUAL
COSINE PATTERN SHADING
CONSTANT TIME DELAY TYPE
BEAM FORMING NETWORK
SCALE - 10db PER INCH
USL Tech Memo No. 932-178-61 of 28 July 1961
FIG 14
CODEX BOOK COMPANY, INC. NORWOOD, MASSACHUSETTS
PRINTED IN U.S.A.
NO 3124 POLAR CO-ORDINATE.



CODEX BOOK COMPANY, INC. NORWOOD, MASSACHUSETTS.
PRINTED IN U.S.A.

NO. 3124. POLAR CO-ORDINATE.

FIG. 15



USL Tech Memo No. 932-178-61 of 28 July 1961

FIG. 16

NO. 3124. POLAR COORDINATE.
CUELLA BOOK COMPANY, INC., NORWOOD, MASSACHUSETTS
PRINTED IN U.S.A.


10°
13°
13db down
18db down
RELATIVE RESPONSE VERSUS BEARING
FREQ 5.50KC (±10%)
12 STAVES KA'S UNEQUAL
COSINE PATTERN SHADING
CONSTANT PHASE SHIFT TYPE
BEAM FORMING NETWORK
SCALE = 10db PER INCH
USL Tech Memo No. 932-178-61 of 28 July 1961
FIG 17



USL Tech Memo No. 932-178-61 of 28 July 1961

FIG 18

NO 3124 POLAR CO-ORDINATE
CODEX BOOK COMPANY, INC., NORWOOD, MASSACHUSETTS
PRINTED IN U.S.A.

K&E 5 X 5 TO THE ½ INCH 359-6
KEUFFEL & ESSER CO. MADE IN U.S.A.



FIG. 19

5 X 5 TO THE ½ INCH 359 8
KEUFFEL & ESSER CO. MADE IN U.S.A.



FIG. 20